



ROOF PLAN
SCALE 3/32" = 1'-0"



Matthew S. Haylock
2/4/11

Roof Plan Notes

ROOF COVERING CLASSIFICATIONS

ALL ROOF COVERINGS SHALL HAVE A MINIMUM CLASS "C" RATING IN ACCORDANCE WITH A.S.T.M. E108.

FLASHING & SEALANTS

PROPER SHEET METAL FLASHING AND SEALANT SHALL BE PROVIDED AND INSTALLED AT ALL ROOF TO ROOF, & ROOF TO WALL JUNCTURES, SKYLIGHT AND MECHANICAL UNIT CURBS, & AT ALL ROOF PENETRATIONS.

ROOF VENTS

THE ROOFING CONTRACTOR SHALL PROVIDE AND INSTALL ROOF VENTS FOR ALL ROOF AREAS. PROVIDE ONE (1) S.F. OF NET CLEAR VENTILATING AREA FOR EACH 150 S.F. OF ROOF AREA.

- 1 TYPICAL TILE ROOFING & ROOF CONSTRUCTION REFER TO BUILDING SECTIONS.
- 2 8 x 5 GUTTER - PREFINISHED ALUMINUM.
- 3 4" DIA. DOWNSPOUT - PREFINISHED ALUMINUM.
- 4 RIDGE VENT - TYPICAL.
- 5 VENT EXHAUST FOR LINEN CHUTE AND DRYER EXHAUST.
- 6 FACE OF BUILDING.
- 7 EYEBROW (TYP.) TILE ROOFING (TYP)
- 8 FALSE CHIMNEY

DATE

FOR PERMIT
2-4-11

1003

A1.5

© COPYRIGHT HAYLOCK DESIGN, INC.
REPRODUCTION OF THE MATERIAL HEREIN, IN PART OR IN WHOLE, WITHOUT WRITTEN CONSENT OF HAYLOCK DESIGN, INC., IS IN VIOLATION OF THE COPYRIGHT LAWS OF THE UNITED STATES AND WILL BE SUBJECT TO LEGAL PROSECUTIONS.